

2444 Baldwin Road, Cleveland, OH 44104 800-662-6338 | PSS-Innovations.com



"When used, temporary ramps shall provide a 12:1

(8.33%) or flatter slope, with a slip-resistant surface. The ramp landing area shall provide a 48-inch x 48inch minimum area with a 2% or flatter cross-slope."

- MUTCD 11th Edition

ADA-COMPLIANT FEATURES:

- » Provides slope of 1" rise for 12" run.
- » Modular edge support castings provide guidance for canes and walking devices. Castings accommodate handrails, which provide detectable guidance.
- » Suspended design allows for normal street drainage.
- » Approach Plates are 48" W x 18" L and feature slipresistant surface.





METAL SECTIONS

- » 3M Anti-Slip Grip Tape along each section
- » Ideal for long-term projects

WOOD SECTIONS

- » Anti-Slip coat on entire board surface
- » Requires maintenance if worn from weather and use

BOARDWALK SYSTEM:

BoardWalk Ramp is a modular, ADA-compliant ramp available in both its original wood design as well as a more durable metal variant.

This system is installed parallel to the curb and provides accessible, detectable, and safe guidance where temporary access routes cross curbs at locations other than permanent sidewalk crossings.

BOARDWALK SYSTEM FEATURES:

- » Wooden or metal sections feature slip-resistant surface
- » Modular edge support castings provide guidance for canes, walking devices, and wheelchairs
- » Designed with movable detectable edge and handrails to accommodate both directions
- » Metal approach plates are 18" W x 48" L with slip-resistant grip tape
- » Wheelchair accessible: 4' W, rated at 800 lb. capacity
- » Handrail couplings from Kee Safety, one of the leading safety solutions suppliers







We don't just talk about Innovations for Safety™ — **we live it.**

PSS | 2444 Baldwin Road, Cleveland, OH 44104 800-662-6338 | PSS-Innovations.com Copyright © 2025 | 07/25 SCAN TO LEARN More About All PSS has to offer

