

CRIB™ ROADQUAKE™ 2F CARRIER

	CRIB-6	CRIB-9	CRIB-12
Dimensions (WxHxL)	19 5/8" x 15" x 74 1/4"	19 5/8" x 19 9/16" x 74 1/4"	19 5/8" x 24 5/16" x 74 1/4"
TPRS Capacity	6	9	12
Weight (Empty)	92 lbs (41 kg)	111 lbs (50 kg)	133 lbs (60 kg)
TPRS Weight	630 lbs (286 kg)	945 lbs (429 kg)	1,260 lbs (572 kg)
Total Weight (TPRS & Carrier)	722 lbs (327 kg)	1,056 lbs (479 kg)	1,393 lbs (632 kg)
Mounting / Receiver	Class IV or V	Class V, or Custom by User	Custom by User
Pintle Mount	Included (2")	Included (2 1/2")	Not Included
Quik-Detach	1 Each Included (Black)	1 Each Included (Blue)	2 Each Included (Black)
Roadquake T-Handle	2 Each Included	2 Each Included	2 Each Included
Guide Markers	36" Included (91 cm)	48" Included (122 cm)	48" Included (122 cm)
Breakaway Pin Kit (1 TPRS)	1 Each Included	1 Each Included	1 Each Included

NOTICE:

UNDERSTAND THE CAPACITIES AND CAPABILITIES OF YOUR VEHICLE PRIOR TO MOUNTING CRIB

ROADQUAKE™ 2F CRIB™ FEATURES:

CRIB is a fully integrated cargo carrier designed specifically for the safe transport, deployment, removal, storage, and safekeeping of RQ2F.

CRIB Carrier Sizes:

- » **CRIB-6** holds six RQ2F
- » **CRIB-9** holds nine RQ2F
- » **CRIB-12** holds twelve RQ2F


Each CRIB carries a multiple of three strips, enough for the deployment and retrieval of up to four, three-strip arrays.

- » Shortens workers' time in traffic to deploy and retrieve strips, compared to manual handling.
- » Deployment and removal of RQ2F can be a one-person job.
- » CRIB mounts to exterior of the vehicle. Strips do not consume space in vehicle.
- » Allows for easier placement of RQ2F in alignment with the deployment location.
- » CRIB eliminates the inverted installation of RQ2F

Patents: <http://bit.ly/3cHVTp8>



RoadQuake™ 2F CRIB™ -6



CRIB-6 FRONT



CRIB-6 BACK

We use the CRIB-6 below to show our new design features, CRIB-9 and CRIB-12 also enjoy the same features.

CRIB FEATURES:


- 1. Guide Fins*:** The fins guide RQ2F in and out of CRIB for easier handling. Stack a max. of four loaded CRIB-6, max. of three CRIB-9, or max. of two CRIB-12.
- 2. Guide Markers:** Provides visual queues when the vehicle is traveling in reverse.
- 3. T-Handle Holder:** CRIB stores and transports two RoadQuake T-Handles, which allow for easier manual lifting of RQ2F.
- 4. Quik-Detach Mounting System:** Expedites the removal and installation of the CRIB Carrier.
- 5. Retractable Ratchet Straps:** Straps extend from attached housing to secure RQ2F strips during transport.
- 6. Literature Canister:** Water-tight canister holds a print copy of our RQ2F Best Practices Guide and a Breakaway Pin Connection Replacement Kit. A Best Practices and pin kit with each CRIB shipment.
- 7. Roller Bearings:** Allow for easier retrieval and deployment of RQ2F in and out of the CRIB.
- 8. QR Code:** Scanning the link on the front label directs to a dedicated web page instructing on appropriate RQ2F spacing.
- 9. "Lift Here" Labels:** Decals on the front of CRIB indicating proper fork placement for forklift transport.

CRIB MOUNTING WITH QUIK-DETACH:

PRODUCT NAME AND IMAGE


QUANTITY AND TYPE OF QUIK-DETACH

CRIB-6




One Black Quik-Detach

CRIB-9



One Blue Quik-Detach

CRIB-12



Two Black Quik-Detach
30" on center

*New CRIB models do not stack with older models.

**Quik Detach for CRIB-6 (black) works for CRIB-6 and CRIB-9. Quik Detach for CRIB-9 (blue) works for CRIB-6, CRIB-9, and CRIB-12.