







SAFETYRAIL™ FEATURES:

SafetyRail is a continuous, interlocking device designed for creating accessible work zones. This device adheres to ADA guidelines and MUTCD 2009 Edition Standards as a sidewalk closure barricade and longitudinal channelizer.

SafetyRail is designed for use with PSS Wave® Guide Rail. The upper Wave Guide Rail is smooth, continuous, and safe for trailing of the hand. The lower Wave Guide Rail measures 1.5" from the ground, reducing potential for trapped cane tips. Wave "notch" design keeps guide rails securely in bushings.

Patents: http://bit.ly/3cHVTp8



SAFETYRAIL FEATURES:

Dimensions: 3.25" W x 38" H x 24" L at base **Weight:** 7 lbs empty or up to 25 lbs with sand

Material: High-density polyethylene plastic, UV inhibitors

MASH Eligibility: SafetyRail: WZ-359 **Wave Guide Rail:** 0.8" x 7.5" x 48" or 72"

High-density polyethylene plastic, UV inhibitors

PSS WAVE GUIDE RAIL:

Available in four-foot or six-foot lengths. Encapsulated ends eliminate cane or hand snagging hazards.

Retroreflective sheeting meets all state and federal specifications and is available in Engineer, Hi-Intensity, and Diamond grades. Wave accepts sheeting on one or both sides.

P55

ATSSA Safer Roads Save Lives



